

Product Specification.

travertine




Travertine

Travertine begins as a calcareous dispersion which is then deposited by hot mineral springs. The result of this method of formation is a honey-combed structure which when finished has visible surface pitting and voids.

Travertine generally comes in either 'cross-cut' or 'vein-cut' formats. Vein-cut tiles are cut so that the surface plane of the tile runs parallel to the long veins present, cross-cut tiles are cut perpendicular to these veins.

Once tiles are cut, they are then either filled with a colour matched resin or left unfilled. Generally, the voids are only left unfilled in Tumbled, Brushed or Split face finishes, where these voids are filled during the grouting process.





UNFILLED



FILLED

Florence

Vein Cut

Size

610 X 305 X 15MM
 610 X 610 X 15MM
 800 X 400 X 15MM
 610 X 305 X 15MM
 610 X 610 X 15MM
 800 X 400 X 15MM
 COPING TILES ON REQUEST
 SLABS ON REQUEST

Finish

UNFILLED & HONED
 UNFILLED & HONED
 UNFILLED & HONED
 FILLED & HONED
 FILLED & HONED
 FILLED & HONED
 VARIOUS
 VARIOUS

Slip

P4
 P4
 P4
 P4
 P4
 P4



Mocha

Cross Cut

Size

610 X 406 X 12MM
 610 X 610 X 12MM
 610 X 406 X 30MM
 FRENCH PATTERN 12MM
 FRENCH PATTERN 30MM



Finish

UNFILLED & TUMBLED
 UNFILLED & TUMBLED
 UNFILLED & TUMBLED
 UNFILLED & TUMBLED
 UNFILLED & TUMBLED

Slip

P5
 P5
 P5
 P5
 P5

Coping Tiles

-  BULLNOSE 610 X 406 X 30MM
-  SQUARE DROP 610 X 406 X 30/50MM

Finish


UNFILLED & TUMBLED
 UNFILLED & TUMBLED

Slip

P5
 P5









UNFILLED



FILLED

Milano

Cross Cut Size

610 X 305 X 15MM
 610 X 610 X 15MM
 800 X 400 X 15MM
 610 X 305 X 15MM
 610 X 610 X 15MM
 800 X 400 X 15MM
 COPING TILES ON REQUEST
 SLABS ON REQUEST

Finish

UNFILLED & HONED
 UNFILLED & HONED
 UNFILLED & HONED
 FILLED & HONED
 FILLED & HONED
 FILLED & HONED
 VARIOUS
 VARIOUS

Slip

P5
 P5
 P5
 P3
 P3
 P3



UNFILLED



FILLED

Milano

Vein Cut
Size

- 610 X 305 X 15MM
- 610 X 610 X 15MM
- 800 X 400 X 15MM
- 610 X 305 X 15MM
- 610 X 610 X 15MM
- 800 X 400 X 15MM
- COPING TILES ON REQUEST
- SLABS ON REQUEST

Finish

- UNFILLED & HONED
- UNFILLED & HONED
- UNFILLED & HONED
- FILLED & HONED
- FILLED & HONED
- FILLED & HONED
- VARIOUS
- VARIOUS

Slip

- P5
- P5
- P5
- P3
- P3
- P3
-
-






Milano Raw

Vein Cut

Size

600 X 300 X 15MM
800 X 400 X 15MM
COPING TILES ON REQUEST

Finish

SAWN & UNFILLED 
SAWN & UNFILLED 
SAWN & UNFILLED 

Slip



Classic

Cross Cut

Size

610 X 305 X 12MM
 610 X 610 X 12MM
 812 X 406 X 12MM
 1220 X 610 X 12MM
 SLABS ON REQUEST

Finish

FILLED & HONED
 FILLED & HONED
 FILLED & HONED
 FILLED & HONED
 VARIOUS

Slip

P5
 P5
 P5
 P5

Coping Tiles


- BULLNOSE 610 X 406 X 30MM
- ⤵ ROUND DROP 610 X 406 X 30/50MM

Finish

FILLED & HONED
 FILLED & HONED

Slip

P5
 P5



Flamingo Pink

Cross Cut

Size

610 X 406 X 12MM
 610 X 406 X 30MM
 FRENCH PATTERN 12MM

Finish

UNFILLED & TUMBLED
 UNFILLED & TUMBLED
 UNFILLED & TUMBLED

Slip

P4
 P4
 P4

Coping Tiles

- ⤵ SQUARE DROP 610 X 406 X 30/50MM


Finish

UNFILLED & TUMBLED

Slip

P4





Noce

Cross Cut

Size

610 X 406 X 12MM
610 X 406 X 30MM
FRENCH PATTERN 12MM
FRENCH PATTERN 30MM



Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P5
P5
P5
P5

Coping Tiles

-  BULLNOSE 610 X 406 X 30MM
-  SQUARE DROP 610 X 406 X 30/50MM

Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P5
P5



Silver Premium

Vein Cut

Size


610 X 305 X 12MM
812 X 406 X 12MM
SLABS ON REQUEST

Finish

FILLED & HONED
FILLED & HONED

Slip

P3
P3



Silver Premium

Cross Cut

Size

305 X 152 X 12MM
610 X 406 X 12MM
812 X 406 X 12MM
610 X 406 X 30MM
610 X 610 X 30MM
FRENCH PATTERN 12MM
FRENCH PATTERN 30MM



Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P4
P4
P4
P4
P4
P4
P4

Coping Tiles

-  BULLNOSE 610 X 406 X 30MM
-  SQUARE DROP 610 X 406 X 30/50MM

Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P4
P4



Silver Standard

Cross Cut

Size

610 X 406 X 12MM
610 X 406 X 30MM
FRENCH PATTERN 12MM
FRENCH PATTERN 30MM

Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P4
P4
P4
P4







Tuscan Raw

Vein Cut

Size

600 X 300 X 20MM
800 X 400 X 20MM

Finish

SAWN & UNFILLED
SAWN & UNFILLED

Slip

P5
P5



Tuscan Premium

Cross Cut

Size

610 X 305 X 12MM
610 X 406 X 12MM
610 X 610 X 12MM
1220 X 610 X 12MM
610 X 406 X 30MM
610 X 610 X 30MM
FRENCH PATTERN 12MM
FRENCH PATTERN 30MM



Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P4
P4
P4
P4
P4
P4
P4
P4

Coping Tiles

-  BULLNOSE 610 X 406 X 30MM
-  SQUARE DROP 610 X 406 X 30/50MM

Finish

UNFILLED & TUMBLED
UNFILLED & TUMBLED

Slip

P4
P4

All tips and guidelines should be taken as general advice and should be used in addition to the relevant Australian standards. These tips and advice are given in good faith. In no way do these replace the service of professional contractors / consultants.

Installation tips.

Before installation

Stone tiles are often packed into crates very tightly, are wet at the point of production and may have some residue from the various finishing processes used. Because of this it is recommended that stone tiles are washed and are allowed to dry completely before every stage of the installation process. They will often lighten in colour as they dry.

It is necessary tiles are dry prior to installation. Dry tiles will show any unusual tonal markings which will indicate where tiles should be placed. At the point of installation always ensure that stone tiles are mixed to ensure an even and consistent distribution of varying patterns. This will mean opening all crates or pallets of materials supplied.

Minor damage such as edge chipping is often caused in packing or unpacking tiles, and should be expected. It is deemed normal practice for these to be used as cuts during the installation.

Stone tiles need to be graded prior to installation; the thicker tiles will dictate the nonlevel and should be installed first. Thinner tiles should be bedded with an appropriate adhesive.

Slight variations in size and thickness can occur with most stones and are deemed acceptable characteristics. All stones should be clean, dry, and free of dust, grease and any loose material before installation.

Make sure that you have discussed your requirements fully with your installer and that they are familiar with the product that is to be fixed.

Please note: All stone should be inspected prior to installation. Stone will have natural occurring variations in colour, texture, chipping and surface finishes. It is these imperfections that make the product unique.

Any tile with excessive chipping, sizing and variation may be subject to a warranty claim. This needs to be done before installation.

Adhesion

All Stone tiles must be solidly bedded, with 100% adhesive coverage.

Tiles should occasionally be lifted during the laying process to ensure that sufficient compaction and full bed adhesion has been achieved.

We recommend Mapei or Laticrete products for the installation process (There are many reputable companies)

au.laticrete.com/

mapei.com/au

Fast setting adhesives are advisable to avoid issues with the moisture retention of some tiles.

Some tiles require the use of specific adhesives to ensure problem-free fixing; please speak to manufactures directly to discuss the requirements of your tile choice.

Light Coloured materials require fixing with white adhesives to prevent possible discoloration within the body of the stone. Flexible adhesives, combined with further substrate preparation, are required when the substrate is wood, or floor. For uncalibrated stone tiles, the appropriate Large Format

Floor Adhesive should be used to accommodate the variation in tile thickness and associated increases in the adhesive bedding. The variation in tile thickness will be most noticeable if laying a mix of sizes in an uncalibrated material.

Grouts

The purpose of grout is to help maintain the stones in their place, create a water tight seam that prevents liquid from seeping into the substrate/adhesive - to its best ability - and to minimise breakages from expansion and contraction.

When grouting it is always recommended to use a high-quality grouting compound that is suitable for the application. Grouting products can be found below.

au.laticrete.com/

mapei.com/au

Please speak to a professional when selecting the correct grout for colour, suitability and durability.

Substrates/foundations/ underfloor heating

The key to preventing problems occurring after tile installation is the correct preparation of the substrate prior to fixing. All substrates that are to be tiled on, floor or wall, should always be suitably prepared. They should be clean, flat, level, free from movement and free from anything which could be deleterious to adhesion.

Correct identification of the substrate is vital to ensure the correct advice and ancillaries are provided. With the increasing use of large format & Split face materials on walls, it is imperative to ensure that the substrate has a suitable weight bearing capability to accommodate the desired material.

For guidelines on fixing to specific substrates please call us for further information. We have a team dedicated in natural stone installations who can help contact the relevant professional (Engineer, architect, building consultant) to produce a work method statement to be specified for the correct substrate, foundations and underfloor heating.

All information required about the stone weight Per/m² can be obtained by contacting us directly.

Cutting

Stone is best cut with a bench saw with a diamond blade. The stone should be washed after cutting to remove all dirt and cutting paste.

Please note that silica dust can be found in natural products and is recommend that safety and health-cautions are used whilst cutting.

Storage

All stone is best stored in a dry area where it will not be affected by the weather. At the very least ensure coverage with a tarp.

Crystalline silica

Commonly known as silica dust this is found in sand, stone, concrete, mortar and variety of products in the construction industry including bricks and plastics. Silica dust particles if exposed can cause health issues.

To prevent and reduce this protective equipment must be worn whilst using tools to cut, grind, drill or other any other procedures that involve manipulating the stone. Safety guidelines relating to silica must be obeyed. For more information, please see the link below.

safeworkaustralia.gov.au/safety-topic/hazards/crystalline-silica-and-silicosis

Sealing

It is crucial to understand that no two pieces are the same when sealing natural stone. Some natural stones are more porous than others, some tend to stain easier, and some manage just fine. When sealing natural stone, it's an industry recommendation that you seal everything on initial application. Doing so will allow you to keep your stone looking beautiful, avoid damages and will allow easier maintenance and cleaning.

Sealing stone can be done by yourself or by a hired professional. The advantage of hiring a professional is the convenience of professional application, cleaning, and preparation. If the job is quite small and you're handy with the tools with the right guidance you should seal it yourself. Please consult our sales staff or accredited sealing companies for a specified sealing system.

Range of sealers to use:

We highly recommend sealing all natural stones to protect and retain its natural beauty for years to come. We recommend using high quality sealers such as Environex, Aqua mix or Dry Treat.

Please note: We provide these recommendations as a service only and will not be responsible for any sealer claims.

- **Aqua Mix**

aquamix.com.au/products/sealers/natural-look-sealers/

- **Environex**

environex.net.au/stonecare/products/sealer-product-selector/ • **Overseal:**

Anti slip treatments

If the desired slip rating cannot be achieved using the product you have selected, you can perform an anti-slip treatment. Please contact RMS or the below companies for more information.

devstonesolutions.com.au/anti-slip

griptek.com.au

Maintenance and cleaning.

Like any surface, stone will require a degree of maintenance. The correct sealing from the start is the key to minimal maintenance.

Heavily tracked areas will require more maintenance than those that are seldom used. The main maintenance regime required for stone is regular sweeping and vacuuming. In addition, the floor should be mopped regularly with a neutral routine cleaner formulated specifically for use with all tiles and natural stone products.

The use of abrasive, acidic or alkali household detergents should be avoided as they can remove the tiles surface sealant or in extreme cases damage stone or porcelain.

Please note: acidic cleaners should not be used, unless professionally recommended.

Always use accredited sealers and cleaners:

- **Aqua Mix**

aquamix.com.au/products/cleaners/

- **Environex**

environex.net.au/stonecare/products/cleaning-product-selector/



naturalstonetiles.com.au

Richmond

(03) 9121 8888

591 Bridge Rd, Richmond

Hoppers Crossing

(03) 9748 7788

6 Nevada Crt, Hoppers Crossing

Geelong

(03) 5261 7777

327 Shannon Ave, Newtown